

Primary Features



[Strong Points of LTK-1600Wide]

- Environment-friendly / Eyesight Protection Product
- Minimized Electricity Consumption
 - / Increased Product Life Span
- Equipped with High Brightness LED of Seoul Semiconductor
- 2 Pieces of Flexible Spring Tube
- Freestyle Head/ A Head Filter for Dazzling Prevention
- Easy Transformation/bound for LED Module
- Dimming Function/Touch Sensor
- Compact Sized Gift Box







Environment Friendly Eye Protection





- * A pollution-free environment-friendly luminous source product
 - Based on functions, not included mercury which is used for fluorescent product, and longer use time to help reduce environmental wastes.
- * Using DC electric power, protect your eye sight.
 - No Lights Blinking







Power Consumption & Life Span



- *6 times cheaper electric cost than the fluorescent bulb
- *6 times longer life span than fluorescent bulb(Semi-permanent)

	Incandesce nt Bulb	Fluorescent	Fluorescent of the Bulb Type	LED
Brightness	General Bright	Normal Bright	Very Bright	Very Bright
Consumption (1,000LM/ 1Hour) *Based on Korean Rate	100W (4 Cent)	40W (1 Cent)	20W (0.5 Cent)	Below 5W (0.1 Cent)
Life Span (5Hours a Day)	1,000 Hours	4,000~ 5,000 Hours	Below 5,000 Hours	From 30,000 To 50,000 Hours







Equipped with High Brightness LED



- * Using Metal PCB and High Brightness SMD Type LED Chip (Seoul Semiconductor LED chip)
 - More Bright, Wider Illuminating Angle
 - LED Quality Assurance due to
 Excellent Protection against heat












2 Pieces of Spring Tube



New Design for the Users' Convenience.

Using 2 Pieces of Flexible Spring Tube, Easy for adjusting the height and angle of Lamp head.










Easy Transformation Bound for LED Module



* Since the luminous source of 4 pieces, not a whole fixed type, gets moved separately, user can shed light the luminous source to the part where you want.(Patent application)










Illumination Distribution Chart



* LTK-1600 Wide Illumination Distribution Chart

측정높이:35cm(서울반도체)

Inside Digit : Brightness / LuxOutside Digit : Distance / mm










Illumination Distribution Chart



* LTK-1600 Wide Illumination Distribution Chart

측정높이:35cm

Inside Digit : Brightness / LuxOutside Digit : Distance / mm









Dimming Function & Touch Sensor



- * Equipped with a DIMMING function which is available to control 3 steps brightness(Off-1-2-3).
- * PWM(Pulse Width Modulation) Touch System
 - : LED Lifetime Extension and Increased Reliability of the Touch Switch.









Packing – Gift Box



*Compact Sized Gift Box

* W * D * H 200 * 200 * 390 mm










Packing – Carton Box



* W * D * H 200 * 200 * 390 mm









Color Variation



Black + Chrome Combination



White + Pink Combination









Color Variation



Wood



Or

Requested

Color

* If you have a special color, MOQ 500pcs / color







CE Certification / RoHS



Declaration of EU RoHS Compliance

The EU Directive(s) covered by this Declarations

2002/93/EEC on the restriction of the use of certain hazardous substances in electrical and dectronic equipment.

Product Name: LED Desk Lamp Model Number(s): LTK-1680 Wide

Supplementary Information.

The basic on which Conformity is being Declared and the Products berevith compiles with the sequirements of RoBS Directive 2002/95/EEC

Remark

- ... Approaching to RoRS Direction, or unitables contrastration value up to 0, M4 be neglekt in homogeneous. materials of electrical and exactronic equipment for leadiffs, mescarefully, hecorebox eleconicos f. 104, polyhyominated hiphenoly PRRef, and polyhyominated diphensh effect (PROE). and up to 0.0000 by need to a specific materials for auditional (d) shall be tolerated.
- The above products have bace compliant since product incaption. We changes have been made in process or nearcials. All products sold under the above PM psecionals, currently and in facure are will be fields compliant with EU Directive 2002/95/EC



103-3210, Bucheon Yechno Park Ssangroughl,

36-1 Samjeong-Dong, Qieong-Gu, Buckeon-City Greenggi-De, Kosca

Tel. +82-70-8355-7051.

Fax. +82-32-424-2259

Seog Jin Kim CEO

http://www.enfeen.com

* CERTIFICADO * CERTIFICAT

Attestation of Compliance No. E8N 10 11 70812 002

Holder of Certificate: ENFREN Co., Ltd.

#103-1210. Sucheon Techno Park Ssangyoung 3th, 36-1, Samjeong-Dong,

Bucheon-City, Gyeongg-Do 421-742 REPUBLIC OF KOREA

Name of Object:

LED lamps LED Desk Lamp

Model(s): EF-200, LTK-1600 and LTK-1600Wide

Description of Object:

Rated input voltage:

(100-240) V a E

Tested

according to:

EN 55015/A1/2007 EN 61547(A1 2000) EN 61000-3-2 2006 EN 61000-3-3/A2:2006

This Attestation of Compliance is saused according to the Directive 2004/100/EC relating to electromagnetic compatibility on a voluntary basis. It confirms that the taked apparatus complex, with all cocondal requirements of the EMC directive and applies only to the sample and its technical documentation submitted to TUV SUD Product Service Cintin for testing and certification. See also notes overlasf.

Test report no.:



Date: 2010-11-05

(Kang-Win Rhee)



ZERTIFIKAT . CERTIFICATE

After preparation of the recessary rechnical documentation as well as the EC conformity documents in the required CE marking can be affected. conformity declaration the required CE marking can be affixed on the product. Other

Page 1 of 1

10V SDO Product Service Center - Zeratzaroneta - RichardraGe ES - BEXES Müschen - Germany







Specification



ltem	Specification	
Light Source	High Brilliant White SMD LED Chip (Seoul Semiconductor LED chip 6pcs LED for each Module – Total 24 pcs LED)	
Brightness / Angle	7,000 mcd (1,200 Lux /35cm from the LED Bulb) / 180 °	
Control Brightness	Dimming Controller [0FF 0.3W - Level 1 2W - Level 2 3W - Level3 5.5W]	
The source of electric power	AC-DC Switching Adaptor (Input:AC100~240V 50/60Hz, Output: DC 12V / 1A)	
Electric Consumption	Max 5W	
Product Size & Weight	Base Ø 17 * Height 400mm * Width 450mm / Weight 1.58kg	
Packing Quantity	20'FT DRY: 1,500 pcs	
Package	LED Desk Lamp, User Manual, AC Adaptor (1.7m)	





